

20" Primary Shutoff



Features:

- Weldable neck available in Carbon, Stainless Steel, and Aluminum
- Lid available in Carbon or Stainless Steel
- 6", 8" or 10" Corrosion Resistant SS Ball Cage
- 4", 6" or 8" Stainless Steel Float Ball
- 2", 3", 4" or 6" NPT Connection
- Wingnut Closure
- 5/8" Square Buna Gasket



Available with Lube Nuts

20" Primary Shutoff

PART NUMBER	DESCRIPTION	WEIGHT
202-2006-3NPT	PSO 20" X 6" CARBON BASE, CARBON LID 3" NPT	80 lbs
202-2006-4NPT-10	PSO 20" X 6" CARBON BASE, CARBON LID 4" NPT, 10" CAGE	89 lbs
202-2006-6NPT	PSO 20" X 6" CARBON BASE, CARBON LID 6" NPT	90 lbs
202-2012-3NPT	PSO 20" X 12" CARBON BASE, CARBON LID 3" NPT	66 lbs
206-2006-2NPT	PSO 20" X 6" ALU NECK, SS LID 2" NPT	55 lbs
206-2006-3NPT	PSO 20" X 6" ALU NECK, SS LID 3" NPT	60 lbs
206-2006-4NPT-10	PSO 20" X 6" ALU NECK, SS LID 4" NPT, 10" CAGE	64 lbs
206-2006-6NPT	PSO 20" X 6" ALU NECK, SS LID 6" NPT	69 lbs
210-2006-2NPT	PSO 20" X 6" SS BASE, SS LID 2" NPT	74 lbs
210-2006-3NPT	PSO 20" X 6" SS BASE, SS LID 3" NPT	80 lbs
210-2009-2NPT	PSO 20" X 9" SS BASE, SS LID 2" NPT	88 lbs
210-2012-2NPT	PSO 20" X 12" SS BASE, SS LID 2" NPT	102 lbs

